

MAPS COMPILATION OF OPEN-PIT MINES BASED ON ORTHOPHOTO TECHNIQUE

Prof. Dr. Zbigniew Sitek
University of Mining and Metallurgy
Al. Mickiewicza 30, Cracow
Poland
Commission IV, W.G. 4

1. Introduction

Increased demand for mineral raw materials as well as exhaustion of easy accessible deposits are reasons to undertake exploitation of deposits with worse raw material parameters and and laying in difficult and worse accessible natural conditions. Therefore in the world, the same as in Poland, large open-pit mines are exploited with deepness from 300 to 900 meters. Work safety, fastness and continuity of surveying information, economy and also necessity of modernization, are the reasons that photogrammetric methods are applied to mining surveying and mapping.

Advantages of orthophotomaps have essential meaning for compilation and revision of mine maps. Orthophotos can be used:

- for compilation and revision of basic, review and special maps of mine surface,
- for volume determination of cap-rock and lignite,
- for planimetric and hight coordinate determination of chosen devices installed at mine,
- for recording of some elements of mine environment.

2. The kind of mining maps

According to Polish Standarts mining maps are divided into: planimetric maps, excavation maps and geological maps. The orthophoto technique, when applied to mapping of open-pit mines, allows compilation of all kinds of planimetric maps and of some excavation maps.

Each of three kinds of mining maps includes: basic maps (usually 1:5000 or 1:10 000), review maps (in practice usually in scale 1:1000 or 1:2000) and the derived or special maps. In cartography, the last ones are called thematic maps.

3. Orthophoto-source for mining map compilation

Considering the applicability of the orthophoto technique to thematic map compilation in open-pit lignite mines, it is necessary to realize what kind of cartographic source of data the orthophoto map is. Orthophoto maps have pictorial qualities of air photos and therefore images of an infinite number of terrain objects can be recognized and identified. The image possesses planimetric correctness, so measurements can be taken directly from an orthophoto just like from a map. The cartographic information from a photographic map is objective and accurate. Images of objects and mining installations are visible with uneven degree of recognition and some of them are hard to identify. But it is important that recognition of such images on orthophoto needs only terrain identification without

any additional measurements. The large scale of orthophoto, scale and quality of air photos ensure visibility of numerous minute details. For open-pit lignite mines the 1:2000 review maps are produced. Orthophotomaps of the same scale can be used for compilation of different kinds of thematic maps.

Having in mind the two-year revision period of basic and review planimetric maps and every quarter revision of analogous excavation maps - the application of the orthophoto technique for production of these maps seems reasonable. The maps can be prepared faster and at lower cost as compared to other techniques. The orthophotomap can serve as the basic source of planimetric information about the state of works in the mine and can be also used for compilation of line or photographic basic and review excavation maps. In case when an orthophotomap is approved as a source of planimetric information about the mine and its surrounding, it can also be used for compilation of basic and review topographic maps, and of the following thematic (special) maps:

- 1 - map of the mining region (planimetric map showing also boundaries of the mining region),
- 2 - map of the industrial district (planimetric map of industrial plants),
- 3 - map of the mining plant (planimetric map with objects and surface and underground installations),
- 4 - map of the transportation routes (planimetric map showing the network of tracks, roads, conveyer-belts and transportation objects),
- 5 - surface energy transfer map (surface map showing power lines and pipe systems of gas, technological steam and compressed air),
- 6 - water and sewage map (surface map showing drinking and industrial water pipelines and sewage system),
- 7 - map of water courses and water basins (surface map showing natural and artificial water basins which could threaten the mining works),
- 8 - map of dumps and stockpiles (showing on a planimetric map stockpiles of useful minerals and dumps of spoil),

Orthophotomaps can be also used for compilation of the another following special maps:

- 9 - maps of terrain displacements (planimetric map with inselines of terrain subsidence),
- 10 - maps of terrain development including development of the area after mining exploitation (planimetric maps showing terrain category and usability for building over),
- 11 - cadastral maps showing boundaries of land use, soil classification, agricultural complexes and of areas, which can be threatened by mining exploitation, draining of water, dust, gases smoke ect.),
- 12 - maps of mining protection pillars (planimetric map with outlines of objects demanding protection - and with borders of protection pillars.

An orthophotomap, in comparison with other maps has a particular advantage: it presents the direct reflection of real positions of objects taken in real time. It is an objective image of reality shown on accurate cartographic base, and therefore it is excellent as a source material for thematic map compilation of open-pit mines. Metrical quality and the rich

content of an orthophotomap are essential for its use as a general base for compilation of thematic maps.




Fig.1a Orthophoto of mining region




Fig.1b Line map of mining region

4. Chosen examples of maps compilation

The range of utilization of the orthophotomap content - is different for various thematic maps. It depends on the degree of recognition of main elements of the thematic map, purpose of the map, and also depends on the formulation and presentation




Fig.2a Orthophoto with transportation routes

of map content. For instance the following derived maps:
1 - the mining region, 2 - the industrial district, 3 - the industrial plant, which shown most of the geographical elements, may be compiled, on the basis of full content of an orthophotomap. Special maps may have the form of a traditional line map or the form of a photographic map with the main elements drafted for better visibility. As an example, several special maps compiled from an orthophotomap are presented in figures 1,2 and 3. Fig. 1a shows a fragment of the orthophoto, which was used for line-map compilation (fig.1b) of a mining region. Fig. 2a and 2b present fragments of the orthophoto and corresponding line map of transportation routes.




Fig.2b Line map of transportation routes

All thematic maps may be compiled directly from orthophoto in form of line-maps as an extraction of some elements or as outline of the same elements directly on the orthophoto base with additional information in the form of conventional signs.

The other derived maps as, for example, surface energy line map - fig. 3b, may be prepared on the basis of orthophoto (fig.3a) in spite of the fact that main elements of these




Fig. 3a Orthophoto with electric power poles supply line




Fig. 3b Map of electrical supply line

thematic maps are hardly distinguishable (see the electric poles on the fig.3a). In such case the orthophotomap may be used for compilation of the thematic map only after interpretation in the terrain. An orthophoto can be also used as an excellent base for compilation of the terrain displacements map.

5. Accuracy remarks

To find out accuracy of the derived maps, their metric quality was determined. The comparison of three kinds of 1:2000 maps was performed on the basis of:

- line map compiled in the C. Zeiss stereoplotter Topocart B using air photos in the scale 1:8000 ($f = 150 \text{ mm}$),
- orthophoto produced in C. Zeiss Orthophot B (from the same air photos),
- derived (from the same orthophoto) line map compiled as an extraction of lines.

For investigation purposes three 1:2000 maps of the same terrain were analysed. Using a digital plotting table and the mentioned above three kinds of maps, the Y-coordinates of selected points was measured. The points were selected at intersections of grid lines (X=0.0 mm, 100 mm, 200 mm, 300 mm, 400 mm and 500 mm) with lines of routes, escarps, ditches and other linear objects. Therefore the chosen points have known X-coordinates and only Y-coordinates are to be measured. For comparison purposes the line map compiled in the Zeiss stereoplotter was used as a reference (with planimetric error of 0,3 mm in the map scale).

Table 1 presents standard errors taken from Y-coordinate differences between the orthophoto and the reference map (A) and between the derived line map and the reference map (B). As can be seen from columns 5 and 6, the errors are $\pm 0,41$ mm and $\pm 0,49$ mm respectively. It is noticeable, that the accuracy of the derived line map is lower than of the orthophoto.

Table 1

List of standard errors of coordinates (in Y-direction)

A - differences between orthophotomap and reference map B - derivative map (compiled from orthophotomap) and reference map					
Indi- ca- tion	Objects	Number of points	Percentage of all points	Before transformation mm	
				A	B
1	2	3	4	5	6
1	Escarps	60	46,5	0,48	0,55
2	Routes	52	40,3	0,35	0,41
3	Ditches	12	9,3	0,42	0,49
4	Other	5	3,9	0,26	0,33
	Together	129	100,0	0,41	0,49

Indi- ca- tion	Objects	After transformation							
		Isometric mm		Helmert's mm		Affine I mm		Affine II mm	
		A	B	A	B	A	B	A	B
		7	8	9	10	11	12	13	14
1	Escarps	0,48	0,55	0,47	0,54	0,47	0,53	0,47	0,53
2	Routes	0,35	0,40	0,35	0,40	0,35	0,40	0,34	0,30
3	Ditches	0,42	0,49	0,41	0,48	0,41	0,48	0,41	0,48
4	Other	0,26	0,33	0,26	0,33	0,26	0,33	0,26	0,33
	Together	0,41	0,48	0,40	0,47	0,40	0,46	0,40	0,46

Of course it is a result of the technology applied. Both maps exceed the demanded accuracy tolerance (standard planimetric error should be less than $\pm 0,4$ mm), although the accuracy of only one coordinate was indicated. But we have to remember, that the presented standard errors are over-estimated as we have assumed errorlessness of the reference map, what is certainly a simplification. Therefore, having in mind the rules of this analysis we should estimate the metric quality of both maps as satisfactory though on the border of demanded accuracy.

The same coordinate measurements were used in the quest of possible systematic errors. The following transformations were used for computations of new coordinates: a) isometric, b) two-dimensional conformal (Helmert's) and two types of two-dimensional affine c) and d).

In general form these transformation can be written as:

$$\begin{bmatrix} X \\ Y \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} + \begin{bmatrix} Tx \\ Ty \end{bmatrix}$$

where: x, y - coordinates measured on the investigated map,
 X, Y - coordinates measured on the reference map,
 T_x, T_y - translation coefficients,
 $a_{11} \dots a_{22}$ - elements of the rotation matrix.

for a) isometric transformation

$$a_{11} = \cos\phi, \quad a_{12} = -\sin\phi, \quad a_{21} = \sin\phi, \quad a_{22} = \cos\phi$$

ϕ - rotation angle between the two coordinate systems

for b) Helmert's transformation:

$$a_{11} = k \cos\phi, \quad a_{12} = -k \sin\phi, \quad a_{21} = k \sin\phi, \quad a_{22} = k \cos\phi$$

k - scale factor

for c) affine transformation I

$$a_{11} = k_x \cos\phi, \quad a_{12} = -k_x \sin\phi, \quad a_{21} = k_y \sin\phi, \quad a_{22} = k_y \cos\phi$$

k_x, k_y - scale factors in x and y directions

for d) affine transformation II

$$a_{11}, a_{12}, a_{13}, a_{14} \text{ - line transformation factors.}$$

The computations gave following results:

- rotation angle: from $0,0075^{\text{a}}$ to $0,0100^{\text{a}}$
- scale factor k : from $1,000290$ to $1,000300$
- scale factor k : from $0,999990$ to $0,999996$
- scale factor k_x^x, k_y^y : from $1,000305$ to $1,000350$
- component of translation T_x : from $0,1$ mm to $0,15$ mm
- component of translation T_y : from $0,3$ mm to $0,4$ mm.

All these values indicate, that the systematic errors do not exist in the analyzed maps (their values are within the limits of tolerance). This is confirmed also by standard errors computed after coordinate transformations (columns 7-14, tab.1) they differ only slightly from standard errors computed without any filtering.