Upscaling the water balance using multiple spatial resolution Earth observations and GIS based agro/eco-hydrological modeling

Eva Boegh, Michael Butts, Per Abrahamsen, Robert Noeddebo Poulsen, Soeren Hansen

Roskilde University Centre

eboegh@ruc.dk

Henrik Soegaard, hs@geogr.ku.dkEbba Dellwik, dellwik@risoe.dkCharlotte Hasager, charlotte.hasager@risoe.dkNiels Otto Jensen, n.o.jensen@risoe.dkJens Christian Loerup, jcl@dhi.dkKim Pilegaard, kim.pilegaard@risoe.dkThe water balance of Sjælland, the major island of Denmark (≈ 7300 km2), is modeled by employing a GIS-based agro/eco-hydrological model (DaisvGIS) and multiple spatial resolution Earth observations for upscaling field level processes. The model setup uses national GIS data to establish a 3-horizontal soil map and pedo/hydrological transfer functions to characterize soil hydraulic properties. The depth to the groundwater is represented by the 10-year average water head elevation which was simulated by the National Water Resource Model (1 km2 grids) and superimposed by a high-resolution wetland map for improved spatial representation of shallow ground waters. Different approaches are employed to model evapotranspiration of the 3 major prevailing surface types; agriculture, forests and urban (impervious) regions that are each parameterized and validated using eddy-covariance flux measurements. A semi-variance analysis is applied to determine an effective spatial resolution for representing surface heterogeneity which is found to be close to 500 m. Vegetation types are mapped using a two-step multi-scale remote sensing based land use classification based on Landsat TM (30 m) and MODIS (500 m) data and validated using national statistics on the area distribution of different crops. Pipe drains are introduced at all clayey agricultural soils and urban regions and agricultural land with shallow groundwater depths by including an aquitard in the setup of these surfaces. The hydraulic conductivity of the aquitard was determined using simple calibration rules rather than calibration data. The model setup is forced using MODIS (500 m) NDVI and 10 km meteorological grid data in 2001 and 2002. Effects of the temporal (hourly, daily) and spatial (30 m, 500 m) resolution were found to be negligible. The yearly pipe flow was found to explain 58 % of the recorded discharge of undisturbed catchments. Finally, the effect of land surface properties and climate variations in 2001 and 2002 on the yearly water balance of Sjælland is discussed.