

## ASSESSING THE POSITIONAL AND THEMATIC ACCURACY OF REMOTELY SENSED DATA

C. A. O. Vieira<sup>a, \*</sup>, P. M. Mather<sup>b</sup>, P. Aplin<sup>b</sup>

<sup>a</sup> Departamento de Engenharia Civil, Universidade Federal de Viçosa, Viçosa, MG, 36570-000, Brazil.  
[carlos.vieira@ufv.br](mailto:carlos.vieira@ufv.br)

<sup>b</sup> School of Geography, The University of Nottingham, Nottingham, NG7 2RD, UK.  
(Paul.Mather, Paul.Aplin)@nottingham.ac.uk

**KEY WORDS:** accuracy, reliability, estimation, representation, error

### ABSTRACT:

Classification of remotely sensed imagery gives variable and often poor quality results. The causes and nature of these errors have been the subject of extensive research. There are two different components of accuracy in the context of remote sensing: positional and thematic accuracy. Positional accuracy determines how closely the position of discrete objects shown on a rectified image (map) or in a spatial database agree with the true position on the ground, while thematic accuracy refers to the non-positional characteristic of a spatial data entity, the so-called attributes (which are derived from radiometric information). Quality control of cartographic products is usually accomplished by computing the discrepancy between well defined points present in one cartographic document with the corresponding points observed in the field, using a technique that guarantees sufficient accuracy for the analysis. In spatial databases generated from remotely sensed data, it is equally necessary the knowledge of discrepancies (errors). However, in some imagery where the number of control points is not sufficient, or where their spatial distribution is suboptimal, the use of generic features (such as roads, edges, polygons, etc) is an important alternative. The aim of this paper is to review standard methods for assessing the quality control of cartographic products in the context of remote sensing. A further aim is to present a methodology to assess the positional accuracy of spatial databases using generic features (and their spatial distribution) within the image in the validation phase, and also describe a methodology that specifically takes into account spatial pattern of errors of omission and commission, in order to present the user with an indication of the reliability of the pixel label assignments. Results show that considerable amount of research and development needs to be accomplished before the spatial characterisation of positional and thematic accuracy associated with remote sensing can be adequately reported in standardised format and legends. Several techniques for the quality control of spatial databases using generic features are adapted to the context of remote sensing, however, one drawback for some of these approaches is the difficult to obtaining homologous points in both representations. Alternative techniques to overtake such limitations are also discussed.

### RÉSUMÉ:

Normalement les images thématiques obtenus par classement des images de satellite présentent un petit niveau de qualité et une précision variable pour la même scène. La raison et nature de ces erreurs sont sujet de plusieurs recherches, avec l'objectif d'améliorer la qualité des produits obtenus par télédétections – images thématiques. Il y a deux composants d'exactitude dans le domaine de télédétections: Précision thématique et précision de position. Précision de position détermine quel est la proximité en face à la position relatif des objets représentée dans une image qui étout corrigé, par relation à sa vrai position dans le terrain tandis que, précision thématique se rapporte à caractéristiques de non position c'est-à-dire aux attributes des images (qui sont dérivés du classement d'images avec utilisation de sa radiométrique). Le contrôle de qualité des produits cartographiques normalement est fait par l'évaluation des divergences entre points de coordonnées bien défini dans un document cartographique et leurs correspondants observé dans le terrain, avec utilisation d'une technique qu'assure la précision de l'analyse. Il est de même importance la connaissance des divergences présentées sur base de données spatiales obtenus des images d'orbite. Cependant, sur quelques images ou le numéro des points de contrôle ne sont pas suffisants ou même leur distribution spatiale ne soit pas convenable l'utilisation de quelques événements (tels que routes, bords, polygones, etc...) représentent une bonne alternative. L'objectif de ce travail de recherche est de réviser les méthodes traditionnels d'évaluation de contrôle de qualité des produits cartographiques dans le contexte de télédétections, Un'autre aspect inédit de cette recherche, est présenter une méthodologie pour évaluer la précision de position des images thématiques avec utilisation des caractéristiques génériques (et leurs distributions spatiales) contenus dans les images dans la phase de validation, et aussi présenter à l'utilisateur une indication de la précision thématique (carte de confiance) des produits de télédétection. Les résultats montrent que une grande quantité de recherches serait nécessaire encore, avant qu'une caractérisation de la précision de position et thématique puisse être touché et standardisées dans le format et légendes. Plusieurs techniques pour le contrôle de qualité de bases de données spatiales en utilisant des caractéristiques génériques ont été adaptées pour être employé dans le contexte de télédétection, cependant, ont désavantage de quelques de ces approches est la difficulté d'obtenir points homologues dans les deux représentations. Quelques techniques alternatives pour dépasser ces limitations sont aussi discutées.

---

\* Corresponding author.

## 1. INTRODUCTION

It is widely acknowledged that classification of remotely sensed imagery has variable and often poor quality. The cause and nature of these errors has been the subject of extensive research in order to improve the accuracy of remotely sensed products. Error in this context can be defined as some discrepancy between the situations depicted on the generated image (map) and reality (Arbia et al., 1998). Performing spatial data analysis operations on data of unknown accuracy will result in a product with low reliability and restricted use in the decision-making process, while errors deriving from one source can propagate through the database via derived products (Lunetta et al., 1991). The quality of data is a function both of the inherent properties of those data and the use to which they are to be put. Hence, knowledge of error levels is necessary if data quality is to be estimated.

There are two different components of accuracy in the context of remote sensing: positional and thematic accuracy (Janssen and Van der Wel, 1994). Positional accuracy determines how closely the position of discrete objects shown on a rectified image (map) or in a spatial database agree with the true position on the ground, while thematic accuracy refers to the non-positional characteristic of a spatial data entity, the so-called attributes (which are derived from radiometric information).

Quality control of cartographic products is usually accomplished by computing the discrepancy between each member of a set of well defined points present in one cartographic document with the corresponding points observed in the field, using a technique that guarantees sufficient accuracy for the analysis. In spatial databases generated from remotely sensed data, it is equally necessary to have knowledge of the discrepancies (errors). However, in some imagery where the number of control points is not sufficient, or where their spatial distribution is suboptimal, the use of generic features (such as roads, edges, polygons, etc) to provide a means of relating two spatial data sets is an important alternative.

The aim of this paper is to review standard methods for assessing the quality of cartographic products in the context of remote sensing. A further aim is to present a methodology to assess the positional accuracy of spatial databases using generic features (and their spatial distribution) within the image in the validation phase, and also present the user with an indication of the thematic reliability of the remote sensing products.

## 2. STUDY AREA AND DATA

Two separate datasets were used in order to assess the positional and thematic accuracy of remote sensing products.

### 2.1 Positional Accuracy

The study area is located near the town of Uberaba-MG, in southeastern Brazil. This area is located at approximately 700m above sea level, and possesses an undulating topography. The economic activities of the region are based on dairy farming, as most of the area is covered by grassland.

Two remotely sensed multi-band images were used in this study, one acquired by the Landsat Thematic Mapper (at 30m resolution) and the other by the High Resolution CCD Camera (HRCCC) carried by the China-Brazil Earth Resources Satellite (CBERS). This camera has a spatial resolution of 20 m. For the purposes of this study, a single waveband of each of the two multi-band images (TM and HRCCC) were used. A 1:25,000 scale map of the study region was used to provide ground reference data.

The two single-band images were geometrically registered to the UTM reference system (zone -23 S) using the Córrego Alegre horizontal datum (Brazil). Image to map registration used 14 and 12 ground control points respectively for the Landsat TM and CBERS HRCCC images, with nearest neighbour resampling, since this technique maintains the original pixel values (Jensen, 1986). In each case, the root-mean-square (RMS) error associated with registration was less than 0.5 pixels (i.e., the RMS for Landsat TM was 0.4721 pixel and the RMS error for the CBERS image was 0.479 pixel). Atmospheric correction was not performed since comparisons are not being made directly between images.

### 2.2 Thematic Accuracy

A SPOT High Resolution Visible (HRV) multispectral (XS) image (14 June 1994) of a region of flat agricultural land located near the village of Littleport (E. England) is used in this study, together with Field Data Printouts for summer 1994. These printouts are derived from survey data supplied by individual farms, and provide details of the crop or crops growing in each field in the study area. On the basis of examination of the areas covered by each crop, the geographical scale of the study, and the spectral separability of the crops, seven crop categories were selected: potatoes, sugar beet, wheat, fallow, onions, peas and bulbs.

Image processing operations were performed using ERDAS Imagine (version 8.0) and the IDRISI GIS. Neural network application used the SNNs software. Some in-house programs were written to carry out specific procedures. Registration of the image to the Ordnance Survey (GB) 1:25,000 map was performed using 17 ground control points and nearest neighbour interpolation. The RMS error was 0.462 pixels.

## 3. TECHNIQUES FOR ESTIMATING POSITIONAL AND THEMATIC ACCURACY

### 3.1 Positional Accuracy

A standard method of assessing the positional accuracy of cartographic products is based on comparison of deviations between homologous control points that can be accurately located on both the reference map and the geometrically corrected image. The deviations at these homologous points are used to compute statistics that are used to perform specific tests to evaluate the accuracy of the geometric corrected image.

An alternative approach to assess the positional accuracy of cartographic products is based on the use of geometric features (Galo et al., 2001). Examples of geometric features are roads, edges, and other boundaries. They should be easily located and represented as a set of sequential coordinates in both documents (i.e., the image to be corrected and the reference map). Three feature-based methods were used by Vieira et al. (2002) to measure the correspondence between features shown on a reference map and a remotely sensed image. These are the Generated Point Method, the Areal Method and the Equivalent Rectangle Method. As these alternative methods work with the relative distances between homologous points, there is no need to apply trend analysis to check the presence of systematic errors on the directions E and N (E and N are the directions X and Y respectively on the Universal Transverse Mercator coordinate system). One of these methods is presented in the following sections.

### 3.1.1 Map Accuracy Standards (MAS) Determination:

An important method for cartographic evaluations of generated maps is the use of Map Accuracy Standards – MAS (Galo et al., 2001), which is based on the comparison of deviations between homologous control points easily located on the reference map ( $X_m, Y_m$ ) and the image ( $X_i, Y_i$ ). The deviations at these homologous points ( $\Delta_E = X_m - X_i, \Delta_N = Y_m - Y_i$ ) are used to compute statistics that are used to perform specific test to evaluate the trend and the accuracy of the geometrically corrected image. In this analysis it was considered that the reference map is sufficiently accurate for our purposes, i.e. to assess the geometric quality of the images.

According to Merchant (1982), the aim of trend analysis is to check for the presence of systematic errors. This check uses the sample mean of the deviations ( $\overline{\Delta_E}, \overline{\Delta_N}$ ). A statistical test is applied, using the null hypothesis that the sample mean is estimating a true (population) mean of zero. If the null hypothesis can be accepted at some significance level then the conclusion to be drawn is that there is no trend or systematic error in the directions  $X$  and  $Y$  respectively.

The Student's  $t$  Test is normally used to carry out this statistical test. The critical value  $t_{n-1, \alpha/2}$  is obtained from statistical tables (where  $n$  is the total number of control points and  $\alpha$  is the confidence level, for example 0.1). If the calculated value of  $t$  for the deviations along the north-south dimension  $|t_N|$  is less than  $t_{n-1, \alpha/2}$  and the calculated value of  $t$  for deviations in the east-west dimension  $|t_E|$  is less than the tabled value  $t_{n-1, \alpha/2}$  then the generated product (e.g., image) is free from systematic errors on the directions  $N$  and  $E$  respectively. The estimated values of  $t_N$  and  $t_E$  can be estimated using the following equations:

$$t_N = (1/\sigma_N) \cdot \Delta_N \cdot n^{1/2} \quad (1)$$

$$t_E = (1/\sigma_E) \cdot \Delta_E \cdot n^{1/2} \quad (2)$$

where  $\sigma_E$  and  $\sigma_N$  are the standard deviations of the discrepancies  $\Delta_E$  and  $\Delta_N$  in the directions  $E$  and  $N$  respectively.

Accuracy analysis uses comparison of the variance of sample deviations ( $\text{var}(\Delta x), \text{var}(\Delta y)$ ) to their respective pre-defined (tabled) values. The test is performed using a hypothesis about the mean and standard deviation of the sample for each of the geometric coordinates. The statistical procedure employed is the Chi-square ( $\chi^2$ ) test. The accuracy of the geometrically corrected image can be estimated separately for the directions  $N$  and  $E$ , using standard statistical methodology involving the comparison of a sample value of  $\chi^2$  ( $\chi^2_{N, n-1}$ ) and the tabled value ( $\chi^2_{n-1, \alpha}$ ), or ( $\chi^2_{E, n-1}$ ) and ( $\chi^2_{n-1, \alpha}$ ) respectively. The values of  $\chi^2_{N, n-1}$  and  $\chi^2_{E, n-1}$  are estimated using the following equations:

$$\chi^2_{N, n-1} = (n-1) \cdot (\sigma_N^2 / \theta_N^2) \quad (3)$$

$$\chi^2_{E, n-1} = (n-1) \cdot (\sigma_E^2 / \theta_E^2) \quad (4)$$

where  $\theta_N$  and  $\theta_E$  are obtained from Table 1 and vary as a function of map scale using the formulae:  $\theta_N = \theta_E = SE / \sqrt{2}$ . The values of the *Standard Error* (SE) for the Brazilian Map Accuracy Standards, for instance, is defined by the decree n° 89.817 of 1984, which classifies cartographic products in relation to their geometric quality (see Table 1).

	MAS	SE	$\theta_N$	$\theta_E$
<b>A</b>	0.5 mm	0.3 mm	21.2132	21.2132
<b>B</b>	0.8 mm	0.5 mm	35.3553	35.3553
<b>C</b>	1.0 mm	0.6 mm	42.4264	42.4264

Table 1. Standard Error (SE) Values for Brazilian Map Accuracy Standards for the scale 1:100.000 (source: Vieira et al., 2002).

**3.1.2 Generated Point Method:** One drawback of some of the standard approaches to quality control of cartographic products is the difficulty of obtaining homologous points in both representations. It is therefore necessary to consider the use of generic features to complement the control points.

The generated point method can be applied to digitised homologous features (i.e., the same features represented in both map and image) in order to generate a set of equally spaced homologous coordinates following the path of both features.

The initial control points for each features should be homologous, so the relative distances (or deviations  $D$ ) between the generated homologous points are used to perform the comparison. It is evident that if there is no deviation between the generated homologous points, the image is well corrected with reference to the map; otherwise, it is necessary to apply statistical analysis in order to check the positional accuracy.

A comparison between the median and standard deviation of these deviations and published Map Accuracy Standards (MAS) are carried out considering a specific scale. The accuracy test uses a Chi-square ( $\chi^2$ ) test based on the specified Standard Error (SE). The geometrically corrected image will be accepted as accurate if  $\chi^2_{D, n-1} < \chi^2_{n-1, \alpha}$ . The sample value of  $\chi^2_{D, n-1}$  can be estimated using equation (5):

$$\chi^2_{D, n-1} = (n-1) \cdot (\sigma_D^2 / \theta_D^2) \quad (5)$$

where, as before,  $\theta_D$  is obtained from the Table 1. However, it is not directional, and separate tests are not carried out for the  $N$  and  $E$  dimensions separately. The value  $\theta_D$  is computed from the formula  $\theta_D = SE / \sqrt{2}$ .

## 3.2 Thematic Accuracy

Current accuracy assessment methods are based on non-spatial statistics derived from the confusion or error matrix, which compares the output of a classifier and known test data (Table 2). These statistics include overall accuracy, individual class accuracy, user's and producer's accuracy, and several other statistics. Although these measures are in widespread use, none of them considers the spatial distribution of erroneously classified pixels, either implicitly or explicitly.

### 3.2.1 Characterising the Spatial Distribution of the Errors:

One possible way to characterise the spatial distribution of the errors in a thematic classification is by generating a "distance image" (see Figure 1(a)) showing the distance from individual pixels to the multivariate means of the classes to which they have been assigned. Either the Euclidean distance or the Mahalanobis distance measure can be used. The former, however, implies spherical clusters in feature space, while the latter takes into account the covariance between the features on which the classification is based. The individual distances are scaled onto a 0-255 range, and displayed as a grey scale image. Darker pixels are spectrally "nearer" to their class centroid (in


CLASSES	PLANIMETRY	SCALE 1:100.000
---------	------------	-----------------

the sense of statistical distance), and are thus more likely to be classified correctly. On the other hand, pixels with higher distance values are spectrally further from the centroid of the class to which they were assigned, and are thus more likely to be misclassified. A threshold can be applied to the distance image to identify those pixels that are most likely to be misclassified.

Classes	Reference Data						TOTAL	Users(%)	Z	K(Cond)	Variance
	1	2	3	4	5	6					
1	344	8	2	1	0	0	355	96.9	87.685	0.863	0.000121
2	33	349	2	2	1	5	392	89	46.767	0.868	0.000345
3	8	21	388	5	5	6	433	89.6	50.784	0.875	0.000297
4	13	20	5	380	0	30	428	85.2	42.548	0.822	0.000373
5	0	1	3	2	394	0	400	98.5	135.018	0.982	0.000053
6	2	1	0	0	0	359	362	99.2	173.393	0.99	0.000033
<b>TOTAL</b>	<b>400</b>	<b>400</b>	<b>400</b>	<b>400</b>	<b>400</b>	<b>400</b>	<b>2400</b>	<b>OVERALL</b>	<b>Z</b>	<b>Kappa</b>	<b>Variance</b>
<b>Producers(%)</b>	<b>86</b>	<b>87.3</b>	<b>97</b>	<b>97.5</b>	<b>98.5</b>	<b>89.8</b>		<b>92.70%</b>	<b>142.937</b>	<b>0.912</b>	<b>0.000041</b>

Table 2. Confusion or error matrix (source Vieira and Mather, 2001).


An alternative way of looking at the spatial distribution of the errors present in a classified image is by directly comparing thematic images with their respective ground truth maps. One of the products of this comparison should be a binary error image (Figure 1(b)) in which each point takes the value 0 (correctly labelled) or 1 (erroneously labelled). By examining the spatial distribution of such pixels in Figure 1 we can make a number of observations. It is apparent that misclassified pixels are spatially correlated. These correlation effects are probably due to the presence of mixed pixels at field boundaries, to variation in the reflectance spectrum caused, most probably, by variations in soil type within a field, or to the effects of crop management practices such as the use of fertilisers. Spatial analysis measures (e.g., Join Count Statistics) could be used in order to determine whether these correlation effects are random or clustered in their spatial distribution. Looking at the spatial distribution of the remaining errors can help to refine the classification process.



(a) Distance Image (b) Error Image

Figure 1. Spatial characterisation of classification errors using thematic image generated by Maximum Likelihood Classifier (385 by 385 pixels).

**3.2.2 Visualising the Reliability:** Any distance measure between the pixel and the mean pixel values (or prototypes) of each class can be used to compute a measure of reliability of a pixel's label. These measures of reliability could be then combined to the already assigned class label in order to generate a new thematic value for the pixel, which not only indicates the class to which the pixels was assigned but also the degree of accuracy achieved. A separate colour is assigned to each class. Within-class levels are also assigned separate shades of that colour, so that each class is represented by five shades of the given colour (see Figure 2(a)). This kind of representation allows the visual appreciation of the degree of accuracy of the classified crop. A contour representation of the reliabilities can also be used (Figure 2(b)). These types of representation help the user to identify portions of the thematic map that have reduced reliability. Although the final map may look uniform in its accuracy, it is actually a representative assemblage from several image processing procedures and refinements. It is important for the user to know how these accuracies are spatially distributed in the image through a thematic reliability map.



(a) Thematic Reliability (b) Reliability Contour Representation

Figure 2. Representation of the reliabilities using a Maximum Likelihood classifier (385 by 385 pixels).

#### 4. RESULTS AND DISCUSSION

A summary of the data used in this study is presented in Table 3.

Table 3. Summary of the mean deviation, standard

Map Accuracy Standards (MAS) Determination					
28 Points Collected.	Image	LANDSAT		CBERS	
	Direction	AE	AN	AE	AN
	Mean	3.5146	-1.7826	-10.9780	2.5555
	Stand Deviations	45.9197	48.0931	46.8662	46.9550
	Max. Errors	80.3581	-85.4290	-94.4135	140.9590
Generated Point Method					
63 Generated Points (Equally spaced)	Distances Between Features (Image-Map)				
	Image	LANDSAT		CBERS	
	Mean	108.3339		76.50388	
	Stand Deviations	30.4817		56.60366	
	Max. Distances	176.8237		237.7162	

deviations used in the Trend and Accuracy analysis; Generated Point method; and Areal and equivalent Rectangles approach.

#### 4.1 Trend Analysis

Trend analysis was carried out using the *Student's t* distribution and a confidence level of 90% ( $\alpha = 0.10$ ). The critical value obtained from statistical table for 28 control points is:  $T_{27, 0.10} = 1.703$ . Using the Equations (1) and (2) in order to compute estimated values of  $t_N$  and  $t_E$ .

**LANDSAT:**

$t_N = 0,1926 < 1,703$  and  $t_E = 0,3977 < 1,703$  (there is no trend in these directions)

**CBERS:**

$t_N = 0,2828 < 1,703$  and  $t_E = 1,2172 < 1,703$  (there is no trend in these directions)

**4.2 Accuracy Analysis**

Accuracy analysis was carried out for both Landsat and CBERS images and the results of the estimates of  $\chi^2_{N,n-1}$  and  $\chi^2_{E,n-1}$ , computed using Equation (3) and (4), the first part of Table 3 and Table 1, are presented in Table 4.

CLASSES	DIRECTIONS	LANDSAT	CBERS
A	E	1.265.172	1.317.865
	N	1.387.768	1.322.864
B	E	455.463	474.432
	N	499.598	476.232
C	E	316.293	329.466
	N	346.942	330.716

Table 4. Estimated values of  $\chi^2_{N,n-1}$  and  $\chi^2_{E,n-1}$  used in the accuracy analysis for the Landsat and CBERS images.

Adopting the critical value of  $\chi^2 = 36,7412$  and considering the limit values for the classes A, B, and C as shown in Table 1 for the Brazilian Map Accuracy Standards (scale 1:100.000), these two images have accuracy equivalent to the class C.

**4.3 Generated Point Method**

The values of the Standard Error (SE) for the generated point method are the same as the Brazilian Map Accuracy Standards, for instance, (see Table 1). As this method works with relative distances between homologous points, there is no need to apply trend analysis to check for the presence of systematic errors in the E and N directions.

The accuracy analysis was also performed for both Landsat and CBERS images using a set of equally spaced homologous coordinates in order to check the positional feature accuracy for a given confidence level. The results are presented in Table 5.

CLASSES	LANDSAT	CBERS
A	128,0141	441,437
B	46,0852	158,918
C	32,0035	110,359

Table 5. Estimated values of  $\chi^2_{D,n-1}$  used in the accuracy analysis for the Landsat and CBERS images

The critical value of  $\chi^2$  is 48.2329 and the limit values are given in Table 1 for the Brazilian Map Accuracy Standards (scale 1:100.000). The Landsat image has an accuracy equivalent to class B, while the CBERS product does not fit in any specify class.

**5. CONCLUSIONS**

Trend analysis indicates that there is no systematic error in any direction for the Landsat and CBERS geometrically corrected images at the 90% confidence level. On the other hand, both

corrected image have an accuracy equivalent to class C using the Brazilian Map Accuracy Standards for a map scale of 1:100.000. Only the Landsat image fits the class B specification, using the generated point method.

These results show that a considerable amount of research needs to be undertaken before the spatial characterization of positional and thematic accuracy associated with remote sensing data can be adequately reported in standardized format and legends. Several techniques for the quality control of spatial databases using generic features are adapted to the context of remote sensing. However, one drawback for some of these approaches is the difficulty in obtaining homologous points in both representations. Alternative techniques for overcoming such limitations could be the use of a spline Fitted method, in which the shape of curves fitted using splines are compared instead of isolated homologous control points (Galo et al., 2001).

**6. ACKNOWLEDGEMENTS**

Preliminary research by Dr. Vieira was supported by the Brazilian Research Council (CAPES). The later stages of this study were conducted as part of the CNPq/COAIE/Kit Enxoval (Project Number 68.0045/01-5) performed in collaboration with The University of Nottingham. We are grateful to Logica PLC, INPE and SPOT Image for permission to use their images.

**7. REFERENCES**

Arbia, G., Griffith, D., and Haining, R., 1998. Error propagation modelling in raster GIS: overlay operations. *International Journal of Geographical Information Science*, 12, pp. 145-167.

Congalton, R. G., and Green, K., 1999. *Assessing the Accuracy of Remotely Sensed Data: Principles and Practices*. Lewis Publishers, New York.

Ferreira, L. F., and Cintra, J. P., 1999. Quantificação de Discrepâncias entre Feições Lineares por Retângulo Equivalente. *Brazilian Magazine of Cartography*, 51, pp. 1-8.

Galo, M., Dal Poz, A. P., and Ferreira, F. M., 2001. Uso de feições no controle de qualidade em cartografia. In *Proceedings of the XX CBC - Cartography Brazilian Congress*, Porto Alegre, 7 - 12 October 2001, <http://www.cartografia.org.br/2001/english/index.html> (accessed 10th Oct. 2001).

Jassen, L. L. F., and van der Wel, F. J. M., 1994. Accuracy assessment of satellite derived land-cover data: a review. *Photogrammetric Engineering and Remote Sensing*, 48, pp. 595-604.

Jensen, J. R., 1986, *Introductory Digital Image Processing – A Remote Sensing Perspective*. Englewood Cliffs, NJ, Prentice-Hall.

Lunetta, R. S., Congalton, R. G., Fenstermaker, L. K., Jessen, J. H., and Mcgwire, K. C., 1991. Remote sensing and geographic information system data integration: error sources and research issues. *Photogrammetric Engineering and Remote Sensing*, 57, pp. 677-687.

Merchant, D. C., 1982. Spatial accuracy standards for large scale line maps. In *Proceedings of the Technical Congress on Surveying and Mapping*, 1, pp. 222-231.

Vieira, C. A. O. and Mather, P. M., 2001. On the assessment of the spatial reliability of thematic images. Ed. Peter J. Halls,

*Innovations in GIS 8: Spatial Information and the Environment*. Taylor and Francis, London, pp. 88-101.

Vieira, C. A. O., and Mather, P. M., 2000. Visualisation of measures of classifier reliability and error in remote sensing In. *ICG ACCURACY 2000, 4th International Symposium on Spatial Accuracy Assessment and Environmental Sciences*, Amsterdam, Delft University Press, pp. 701-708.

Vieira, C. A. O., Mather, P. M., and Borges, P. A. F., 2002. Assessing the positional accuracy of remotely sensed products In. *5th International Symposium on Spatial Accuracy Assessment in Natural Resources and Environmental Sciences*, Melbourne, Australia, 2002.